

SAMMYS SWIVEL HEAD™ FOR CONCRETE - Swivel Application



MADE WITH Tapcon

Application	Product Features
	<ul style="list-style-type: none"> • Installs vertically and swivels up to 89° in wood & concrete structures. • Eliminates distortion of threaded rod. • 1/4" pre-drilled pilot hole required. • Concrete installation tool available for a one piece installation process. • Made in the U.S.A.



#14 SH Orange Nut Driver Part # 8273910

Approvals	Rod Size	Part Number	Model	Screw Descriptions	Ultimate Pullout (lbs)*	Box Qty	Case Qty
SWIVEL MOUNT							
	3/8"	8269957	SH-GST/CST 20	5/16 x 1-3/4"	2537 in 3000 psi concrete 1459 @ 45° off vertical in 3000 psi concrete 2852 in 6000 psi concrete 1636 @ 45° off vertical in 6000 psi concrete	25	125
	1/2"	8303957	SH-GST/CST 2.0	5/16 x 1-3/4"	2537 in 3000 psi concrete 1459 @ 45° off vertical in 3000 psi concrete 2852 in 6000 psi concrete 1636 @ 45° off vertical in 6000 psi concrete	25	125

Note: UL Listed for wood - see page 5

* Tested in 3000 PSI concrete

CONCRETE / WOOD INSTALLATION KIT



Application	
<p>Rotary Hammer Drill into concrete</p>	<p>Hammer Drill into concrete</p>

Part Number	Description	Each Qty
8122910	Concrete Installation Kit (a)	
Kit includes the following items:		
8113910	#14 Black Nut Driver (b)	1
8114910	#14 SW Red Nut Driver (c)	1
8116910	#250 Bit (1/4") (d)	1
8117910	SDS Bit (1/4") (e)	1
8118910	7/32 Wood Bit (f)	1
8120910	HEX 250 Bit Receiver (1/4") (g)	1
8098910	SL 250 Sleeve (h)	1
8121910	SDS B250 Bit Receiver (1/4")*	1

*Only sold separately - not included in kit.