

DEKTITE® AND RETROFIT DEKTITE® Pipe Flashings

The original flexible pipe flashing system with a 20 year warranty.



Applications

- Plumbing, Heating, Air Conditioning, Electrical and Exhaust Vents.

Product Features


- Made of long life, flexible, weatherproof gray EPDM rubber or red silicone.
- Flexible, corrosion resistant aluminum base conforms to any panel configuration.
- EPDM and silicone will not crack or break.
- Pipe diameter markings are clearly indicated for accurate fitting.
- Designed for 1/4" to 18" diameter pipes.
- One piece construction is easy to install.
- Pleated cone adjusts to any roof pitch and allows for complete flexibility.
- EPDM has a continuous service temperature range of -65°F to +250°F (grey in color).
- Silicone has a continuous service temperature range of -40°F to +350°F (red in color).
- Proven resistance to ozone and ultra-violet light.

Product Specifications


Pipe Diameter Ranges.....1/4" to 13" - Dektite
 3/4" to 7-1/4" - Retrofit Dektite
 7" to 18" - Silicone

Materials.....EPDM - Standard and Retrofit
 Silicone - High Temperature


Dektite Installation Guidelines




STEP 1: Cut Dektite at appropriate pipe diameter marking.




STEP 2: Slide Dektite flashing down over pipe.



STEP 3: Apply sealant on underside of flexible aluminum base.



STEP 4: Press Dektite base into contours of panel configuration.




STEP 5: Fasten Dektite to surface with Buildex Scots® self-drilling fasteners. Apply additional sealant around base if desired.

- Notes:**
- Dektite can be installed over or between the ribs of standard panels.
 - DO NOT** install over SSR or architectural panel seams.
 - Generally no sealant is required where the Dektite collar provides a compression fit around the pipe. However, some metal pipes and flues include a seam which may require a local application of sealant at the point where the Dektite collar crosses the seam.


DEKTITE® & RETROFIT DEKTITE® PIPE FLASHINGS

Selector Guide

Dektite Flashing Guide					
Part Number	Description	Pipe Outside Diameter	Dektite Base Diameter	Dektite Height	Box Quantity
4003910	1	1/4"-2"	4-3/4"	3"	10
4004910	2	1-3/4"-3-1/4"	6-1/4"	4"	10
4009910	3	1/4"-5"	7-3/4"	4"	10
4011910	4	3"-6"	9-1/4"	5"	10
4016910	5	4" - 7"	10-3/4"	5"	5
4025910	8	7" - 13"	16-1/2"	6"	5
4038910	#8 Silicone	7" - 13"	16-1/2"	6"	5



Standard Dektite



Retrofit Dektite

Part Number	Description	Box Qty
1175153	1/4-14 x 1-1/8" Scots Teks1	2,500

Retrofit Dektite Selector Guide					
Part Number	Dektite Size Number	Pipe Outside Diameter	Dektite Base Diameter	Dektite Height	Box Qty
4029910	801	3/4"-2-	3-1/4"-	10-3/4"	5-3/5"
4030910	802	3/4"	10"	14-1/2"	5-4/5"
4031910	803	2"-7-1/4"	6-3/10"	3-1/2"	10


Note: When used on roofs where pitch is steeper than 20 degrees, or when used on deep ribbed profile roof panel (1-1/2" deep corrugation or more), consider using next larger size Dektite that will accommodate the same pipe diameter.

Performance Data


ASTM Method	Test Description	Specification	Test Results
D412	Tensile Strength (min. psi rating)	1450 psi min.	1537 psi
D412	Ultimate Elongation (%)	350 min.	535
D1171	Resistance to Ozone-min. rating	100 (no cracks)	Passed
D673	Heat Aging - 70 hrs. at 212°F		
	• Change in Hardness (points)	± 15 max.	+8
	• Change in Tensile Strength (%)	± 30 max.	-4.7
	• Change in Elongation (%)	± 50 max.	-26

ASTM Method	Test Description	Specification	Test Results
D2137	Low Temperature Brittleness-3 mins. at -40°F	Non-brittle	Passed
D624	Tear Resistance Die C (min.) per inch of width min.	125 pounds per inch of width	130 pounds
U.L. 94	Flame Resistance	U.L. 94 H.B.	Passed


Retrofit Dektite Installation Guidelines




STEP 1: Begin cutting opposite of the mechanical locking jointer. Cut through the jointer with tin snips.




STEP 2: Wrap Retrofit Dektite around the pipe. Engage the top section of the jointer first, then proceed down until jointer is completely engaged.




STEP 3: Crimp jointer tightly, starting at the top by squeezing jointer "fingers" with pliers.



STEP 4: Apply sealant to the underside of the ribbed aluminum base. Press Retrofit Dektite against contours of the panel configuration.



STEP 5: Attach Retrofit Dektite to the panel with SCOTS® self-drilling screws. Screws should be spaced as necessary to avoid gaps between the base and the panel.



STEP 6: Apply additional sealant around the top of the Dektite, near the mechanical locking jointer seam.

Recommended Sealant: Chemseco Sikaflex® sealant, part number 4040910.



700 High Grove Blvd
Glendale Heights, Illinois 60139
800-848-5611 Fax: 630-595-3549
www.itwbuildex.com

Teks® and Climaseal® are trademarks of Illinois Tool Works, Inc.
Dekship® and Dektite® are registered trademarks of Dek Industries
© 2019 Illinois Tool Works, Inc.